



Quick Look

Number of Ethernet WAN port	1 / 0 (GE) ^[1]	[1] WAN port(s) can be configured as LAN port(s) via the Web Admin.
Number of Ethernet LAN port	1 / 2 (GE) ^[1]	[1] WAN port(s) can be configured as LAN port(s) via the Web Admin.
Router Throughput	400Mbps ^[2]	[2] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (No Encryption)	100Mbps ^[2]	[2] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (256-bit AES)	60Mbps ^[2]	[2] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
Number of Cellular Modem	1	

Interfaces

Maximum Ethernet WAN / LAN port configuration	1 WAN with 1 LAN, 0 WAN with 2 LAN
SFP LAN / WAN	No
Serial Interface	Yes
Wi-Fi AP	Yes
Wi-Fi WAN	Yes
USB WAN	No

Module Expansion	No
------------------	----

Performance

Number of Recommended Users	25–150
-----------------------------	--------

Maximum Number of Controlled AP / Switch	30 / 50 ^[3]
--	------------------------

[3] 50 AP is available as a license add-on (AP-LC-50).

Wireless details

Cellular Modem Category options	1x CAT-4, 1x CAT-6, 1x CAT-12, 1x CAT-18, 1x 5G
---------------------------------	---

5G support	Yes
------------	-----

SIM Slots	2
-----------	---

SIM Card Size	Mini-SIM (2FF)
---------------	----------------

Wi-Fi Radio	Dual (2.4GHz + 5GHz), 2x2 Wi-Fi 5
-------------	--------------------------------------

Wi-Fi Antenna Transmit Power (2.4GHz, single chain)	19dBm
---	-------

Wi-Fi Antenna Transmit Power (5GHz, single chain)	21dBm
---	-------

Multiple SSIDs	16
----------------	----

GPS	Yes
-----	-----

RemoteSIM (used in SIM Injector)	No
----------------------------------	----

FusionSIM	No
-----------	----

Peplink eSIM Data Plans	No
-------------------------	----

BYO eSIM	No
----------	----

Features

SpeedFusion Hot Failover	Yes ^[4]	[4] Require PrimeCare Subscription, complimentary for the first year.
SpeedFusion Smoothing	Yes ^[4]	[4] Require PrimeCare Subscription, complimentary for the first year.
SpeedFusion Bandwidth Bonding	Yes ^[4]	[4] Require PrimeCare Subscription, complimentary for the first year.
SpeedFusion Connect	Yes ^[5]	[5] CarePlan subscription includes 500 GB/year complimentary SpeedFusion Connect Usage data.
SpeedFusion Relay Mode (Server)	Yes	
Drop-In Mode	Yes	
High Availability	Yes	
Peplink AP Series Management	Yes	
Remote AP & Multiple Config Profiles Management	No	
Switch Controller	Yes	
WAN as LAN	Yes	
LAN Bypass	No	
InTouch	Yes	
Virtual WAN	Yes ^[6]	[6] Up to 3 Virtual WAN if purchasing Virtual WAN Activation Licence.
Synergy Mode (Controller)	Yes	
Synergized Device	Yes	
Application and Web Blocking	Yes	
Web Content Filtering	Lite	
IP Passthrough	Yes	
IPv6	Yes	

x.509 Certificate	No
Captive Portal	Yes
GPIO	No
Ignition Sensing	No
Netflow Support	Yes
LACP (802.3ad) NIC Bonding	No
Jumbo Frame Support	No
Internal Storage for Edge Computing	No
External Storage via USB Port	No
Dead Reckoning	No

Core Functionality

Inter-VLAN Routing	Yes
802.1q VLANs Supported	128
Port-Based VLAN	Yes
Load Balancing Algorithms	8
Load Balancing & Failover	Yes
Inbound Load Balancing	No
InControl 2 Cloud Management	Yes
InControl GPS Fleet Management	Yes

Advanced QoS Functionality

Bandwidth Usage Monitoring	Yes
----------------------------	-----

QoS for VoIP and E-Commerce	Yes
-----------------------------	-----

User Groups Bandwidth Control	Yes
-------------------------------	-----

VPN Functionality

SpeedFusion VPN	Yes
-----------------	-----

Number of SpeedFusion VPN Peers	2 or 5 ^[7]
---------------------------------	-----------------------

[7] 2 SpeedFusion VPN Peers are enabled by default. 5 SpeedFusion VPN Peers are enabled with PrimeCare Subscription, complimentary for the first year.

IPsec VPN	Yes
-----------	-----

Number of IPsec Tunnels	5
-------------------------	---

L2TP VPN / Open VPN / PPTP VPN Server	Yes
---------------------------------------	-----

Maximum PPTP / L2TP / OpenVPN Users	3
-------------------------------------	---

Remote RADIUS / LDAP authentication in Remote User Access	No
---	----

Number of OpenVPN Tunnel (Site to Site)	5
---	---

Number of GRE Tunnel (Site to Site)	5
-------------------------------------	---

Hardware

Enclosure	Indoor, Metal
-----------	------------------

4pin Molex Micro-Fit Connector	No
--------------------------------	----

Terminal Block Power Connector for Mobile / Vehicular Deployment	Yes
--	-----

AC Adapter or PSU	AC Input 100V–240V, DC Output 12V 2A
-------------------	---

Input voltage	DC 12–48V
---------------	-----------

PoE Input	No
PoE Output	No
USB Power Input	No
Nominal Power Consumption	7.5W
Maximum Power Consumption	18W
Dimensions in inches	6.3 x 3.8 x 1.3 inches
Dimensions in mm	160 x 97 x 33.5 mm
Weight (Pound)	1.3 pounds
Weight (Gram / Kilogram)	590 grams
Operating Temperature	-40°–149°F, -40°–65°C
Humidity	15%–95% (non-condensing)
Rack-mount	No
Dual Hot Swap Power Supply	No

Warranty Info

Warranty	1-Year Limited Warranty
----------	-------------------------