



Quick Look

Number of Ethernet WAN port	2 (GE)	
Number of Ethernet LAN port	4 (GE)	
Router Throughput	200Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (No Encryption)	120Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (256-bit AES)	55Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
Number of Cellular Modem	1	

Interfaces

Maximum Ethernet WAN / LAN port configuration	2 WAN with 4 LAN
SFP LAN / WAN	No
Serial Interface	No
Wi-Fi AP	No
Wi-Fi WAN	No
USB WAN	Yes (1x USB)

Module Expansion	No
------------------	----

Performance

Maximum Number of Controlled AP / Switch	30 / 50 ^[2]	[2] 50 AP is available as a license add-on (AP-LC-50).
Number of Recommended Users	1-60	

Wireless details

Cellular Modem Category options	1x CAT-4
5G support	No
SIM Slots	No
SIM Card Size	Mini-SIM (2FF)
Wi-Fi Radio	No
Wi-Fi Antenna Transmit Power (2.4GHz, single chain)	No
Wi-Fi Antenna Transmit Power (5GHz, single chain)	No
Multiple SSIDs	No
GPS	No
RemoteSIM (used in SIM Injector)	No
FusionSIM	No
Peplink eSIM Data Plans	No
BYO eSIM	No

Features

SpeedFusion Hot Failover	No
--------------------------	----

SpeedFusion Smoothing **No**SpeedFusion Bandwidth Bonding **No**SpeedFusion Connect **Yes** ^[3]

[3] CarePlan subscription includes 500GB/year complimentary SpeedFusion Connect Usage data.

SpeedFusion Relay Mode (Server) **Yes**Drop-In Mode **Yes**High Availability **Yes**Peplink AP Series Management **Yes**Remote AP & Multiple Config Profiles Management **No**Switch Controller **Yes**WAN as LAN **No**LAN Bypass **No**InTouch **Yes**Virtual WAN **Yes** ^[4]

[4] Up to 3 Virtual WAN if purchasing Virtual WAN Activation Licence.

Synergy Mode (Controller) **Yes**Synergized Device **Yes**Application and Web Blocking **Yes**Web Content Filtering **No**IP Passthrough **No**IPv6 **Yes**x.509 Certificate **Yes**Captive Portal **Yes**

GPIO	No
Ignition Sensing	No
Netflow Support	Yes
LACP (802.3ad) NIC Bonding	No
Jumbo Frame Support	No
Internal Storage for Edge Computing	No
External Storage via USB Port	No
Dead Reckoning	No

Core Functionality

Inter-VLAN Routing	Yes
802.1q VLANs Supported	16
Port-Based VLAN	Yes
Load Balancing & Failover	Yes
Load Balancing Algorithms	8
Inbound Load Balancing	No
InControl 2 Cloud Management	Yes
InControl GPS Fleet Management	No

Advanced QoS Functionality

Bandwidth Usage Monitoring	Yes
QoS for VoIP and E-Commerce	Yes
User Groups Bandwidth Control	Yes

VPN Functionality

SpeedFusion VPN	Yes	
Number of SpeedFusion VPN Peers	3 or 5 ^[5]	[5] PepVPN/SpeedFusion Peers license, it can change the maximum number of PepVPN/SpeedFusion peer.Balance 30 LTE, PVN-LC-05. Up to 5 PepVPN/SpeedFusion peers.
IPsec VPN	Yes	
Number of IPsec Tunnels	5	
L2TP VPN / Open VPN / PPTP VPN Server	Yes	
Maximum PPTP / L2TP / OpenVPN Users	15	
Remote RADIUS / LDAP authentication in Remote User Access	No	
Number of OpenVPN Tunnel (Site to Site)	5	
Number of GRE Tunnel (Site to Site)	5	

Hardware

Enclosure	Indoor, Metal
4pin Molex Micro-Fit Connector	No
Terminal Block Power Connector for Mobile / Vehicular Deployment	No
AC Adapter or PSU	12V 3A PSU (ACW-602)
Input voltage	DC 12V
PoE Input	No
PoE Output	No



USB Power Input	No
Nominal Power Consumption	NA
Maximum Power Consumption	28W
Dimensions in inches	10.2 x 5.24 x 1.38 inches
Dimensions in mm	260 x 133 x 35 mm
Weight (Pound)	2.2 pounds
Weight (Gram / Kilogram)	1 kg
Operating Temperature	-40°-149°F, -40°-65°C
Humidity	NA
Rack-mount	No
Dual Hot Swap Power Supply	No

Warranty Info

Warranty	1-Year Limited Warranty
----------	-------------------------