



Quick Look

Number of Ethernet WAN port	1 (GE)	
Number of Ethernet LAN port	4 (GE)	
Router Throughput	120Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (No Encryption)	40Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (256-bit AES)	20Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
Number of Cellular Modem	1	

Interfaces

Maximum Ethernet WAN / LAN port configuration	1 WAN with 4 LAN
SFP LAN / WAN	No
Serial Interface	No
Wi-Fi AP	Yes
Wi-Fi WAN	Yes
USB WAN	No

Module Expansion	No
------------------	----

Performance

Number of Recommended Users	1–60
-----------------------------	------

Maximum Number of Controlled AP / Switch	No
---	----

Wireless details

Cellular Modem Category options	1x CAT-4, 1x CAT-6
---------------------------------	-----------------------

5G support	No
------------	----

SIM Slots	2
-----------	---

SIM Card Size	Mini-SIM (2FF)
---------------	----------------

Wi-Fi Radio	Dual (2.4GHz + 5GHz), 2x2 Wi-Fi 4
-------------	--------------------------------------

Wi-Fi Antenna Transmit Power (2.4GHz, single chain)	26dBm
--	-------

Wi-Fi Antenna Transmit Power (5GHz, single chain)	25dBm
--	-------

Multiple SSIDs	16
----------------	----

GPS	Yes
-----	-----

RemoteSIM (used in SIM Injector)	Yes (HW5+)
----------------------------------	------------

FusionSIM	Yes (HW5+)
-----------	------------

Peplink eSIM Data Plans	No
-------------------------	----

BYO eSIM	No
----------	----

Features

SpeedFusion Hot Failover	Yes
SpeedFusion Smoothing	Yes
SpeedFusion Bandwidth Bonding	No
SpeedFusion Connect	Yes (HW2+) ^[2]
SpeedFusion Relay Mode (Server)	Yes
Drop-In Mode	Yes
High Availability	Yes
Peplink AP Series Management	No
Remote AP & Multiple Config Profiles Management	No
Switch Controller	No
WAN as LAN	No
LAN Bypass	No
InTouch	Yes (HW2+)
Virtual WAN	No
Synergy Mode (Controller)	No
Synergized Device	Yes (HW2+)
Application and Web Blocking	Yes
Web Content Filtering	Lite
IP Passthrough	Yes
IPv6	No
x.509 Certificate	No

[2] CarePlan subscription includes 500 GB/year complimentary SpeedFusion Connect Usage data.

Captive Portal	Yes
----------------	-----

GPIO	Yes
------	-----

Ignition Sensing	Yes
------------------	-----

Netflow Support	No
-----------------	----

LACP (802.3ad) NIC Bonding	No
----------------------------	----

Jumbo Frame Support	No
---------------------	----

Internal Storage for Edge Computing	No
-------------------------------------	----

External Storage via USB Port	No
-------------------------------	----

Dead Reckoning	No
----------------	----

Core Functionality

Inter-VLAN Routing	Yes
--------------------	-----

802.1q VLANs Supported	16
------------------------	----

Port-Based VLAN	Yes
-----------------	-----

Load Balancing Algorithms	8
---------------------------	---

Load Balancing & Failover	Yes
---------------------------	-----

Inbound Load Balancing	No
------------------------	----

InControl 2 Cloud Management	Yes
------------------------------	-----

InControl GPS Fleet Management	Yes
--------------------------------	-----

Advanced QoS Functionality

Bandwidth Usage Monitoring	Yes
----------------------------	-----

QoS for VoIP and E-Commerce	Yes
-----------------------------	-----

User Groups Bandwidth Control	Yes
-------------------------------	-----

VPN Functionality

SpeedFusion VPN	Yes
-----------------	-----

Number of SpeedFusion VPN Peers	2 or 5 ^[3]
---------------------------------	-----------------------

[3] Require license to increase maximum number of PepVPN/SpeedFusion Peers. Several option are available based on the model 5, 10 or 20 peers (PVN-LC-05, PVN-LC-10, PVN-LC-20).

IPsec VPN	Yes
-----------	-----

Number of IPsec Tunnels	5
-------------------------	---

L2TP VPN / Open VPN / PPTP VPN Server	Yes
---------------------------------------	-----

Maximum PPTP / L2TP / OpenVPN Users	3
-------------------------------------	---

Remote RADIUS / LDAP authentication in Remote User Access	No
---	----

Number of OpenVPN Tunnel (Site to Site)	5
---	---

Number of GRE Tunnel (Site to Site)	5
-------------------------------------	---

Hardware

Enclosure	Compact, Indoor Metal
-----------	--------------------------

4pin Molex Micro-Fit Connector	Yes
--------------------------------	-----

Terminal Block Power Connector for Mobile / Vehicular Deployment	Yes
--	-----

AC Adapter or PSU	AC Input 100V–240V, DC Output 12V 2A
-------------------	---

Input voltage	DC 12–28V
---------------	-----------

PoE Input	No
-----------	----

PoE Output	No
USB Power Input	No
Nominal Power Consumption	NA
Maximum Power Consumption	25W
Dimensions in inches	1.6 x 10.2 x 5.6 inches
Dimensions in mm	40 x 260 x 143 mm
Weight (Pound)	2.65 pounds
Weight (Gram / Kilogram)	1.2 kg
Operating Temperature	-40°–149°F, -40°–65°C
Humidity	15%–95% (non-condensing)
Rack-mount	No
Dual Hot Swap Power Supply	No

Warranty Info

Warranty	1-Year Limited Warranty
----------	-------------------------