



Quick Look

Number of Ethernet WAN port	2 (GE)	
Number of Ethernet LAN port	4 (GE)	
Router Throughput	400Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (No Encryption)	120Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (256-bit AES)	55Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
Number of Cellular Modem	2	

Interfaces

Maximum Ethernet WAN / LAN port configuration	2 WAN with 4 LAN
SFP LAN / WAN	No
Serial Interface	No
Wi-Fi AP	Yes
Wi-Fi WAN	Yes
USB WAN	Yes (1x USB)

Module Expansion	No
------------------	----

Performance

Number of Recommended Users	25–150
-----------------------------	--------

Maximum Number of Controlled AP / Switch	30 / 50 ^[2]
--	------------------------

[2] 50 AP is available as a license add-on (AP-LC-50).

Wireless details

Cellular Modem Category options	2x CAT-4, 2x CAT-6, 1x CAT-6 + 1x CAT-12
---------------------------------	--

5G support	No
------------	----

SIM Slots	2, (no redundant slots)
-----------	----------------------------

SIM Card Size	Mini-SIM (2FF)
---------------	----------------

Wi-Fi Radio	Dual (2.4GHz + 5GHz), 2x2 Wi-Fi 5
-------------	--------------------------------------

Wi-Fi Antenna Transmit Power (2.4GHz, single chain)	23dBm
---	-------

Wi-Fi Antenna Transmit Power (5GHz, single chain)	21dBm
---	-------

Multiple SSIDs	16
----------------	----

GPS	Yes
-----	-----

RemoteSIM (used in SIM Injector)	No
----------------------------------	----

FusionSIM	No
-----------	----

Peplink eSIM Data Plans	No
-------------------------	----

BYO eSIM	No
----------	----

Features

SpeedFusion Hot Failover	Yes
SpeedFusion Smoothing	Yes
SpeedFusion Bandwidth Bonding	Yes
SpeedFusion Connect	Yes
SpeedFusion Relay Mode (Server)	Yes
Drop-In Mode	Yes
High Availability	Yes
Peplink AP Series Management	Yes
Remote AP & Multiple Config Profiles Management	No
Switch Controller	Yes
WAN as LAN	No
LAN Bypass	No
InTouch	Yes (HW5+)
Virtual WAN	Yes (HW5+) ^[3]
Synergy Mode (Controller)	Yes (HW5+)
Synergized Device	Yes
Application and Web Blocking	Yes
Web Content Filtering	Lite
IP Passthrough	Yes ^[4]
IPv6	Yes
x.509 Certificate	Yes
Captive Portal	Yes

^[3] Up to 3 Virtual WAN upon purchasing Virtual WAN Activation Licence.

^[4] Available for Firmware 8.5.0 or above.

GPIO	No
Ignition Sensing	No
Netflow Support	Yes
LACP (802.3ad) NIC Bonding	No
Jumbo Frame Support	No
Internal Storage for Edge Computing	No
External Storage via USB Port	No
Dead Reckoning	Yes

Core Functionality

Inter-VLAN Routing	Yes ^[4]	[4] Available for Firmware 8.5.0 or above.
802.1q VLANs Supported	128	
Port-Based VLAN	Yes	
Load Balancing Algorithms	8	
Load Balancing & Failover	Yes	
Inbound Load Balancing	No	
InControl 2 Cloud Management	Yes	
InControl GPS Fleet Management	Yes	

Advanced QoS Functionality

Bandwidth Usage Monitoring	Yes
QoS for VoIP and E-Commerce	Yes
User Groups Bandwidth Control	Yes

VPN Functionality

SpeedFusion VPN	Yes	
Number of SpeedFusion VPN Peers	2 or 5 or 20 ^[5]	[5] Require license to increase maximum number of PepVPN/SpeedFusion Peers. Several option are available based on the model 5, 10 or 20 peers (PVN-LC-05, PVN-LC-10, PVN-LC-20).
IPsec VPN	Yes	
Number of IPsec Tunnels	5	
L2TP VPN / Open VPN / PPTP VPN Server	Yes	
Maximum PPTP / L2TP / OpenVPN Users	15	
Remote RADIUS / LDAP authentication in Remote User Access	Yes	
Number of OpenVPN Tunnel (Site to Site)	5	
Number of GRE Tunnel (Site to Site)	5	

Hardware

Enclosure	Indoor, Metal	
4pin Molex Micro-Fit Connector	No	
Terminal Block Power Connector for Mobile / Vehicular Deployment	Yes	
AC Adapter or PSU	AC Input 100V–240V, DC Output 12V 3A	
Input voltage	DC 10–56V	
PoE Input	No	
PoE Output	Up to 4x 802.3af PoE ^[6]	[6] Require PoE Activation Kit. Includes power supply and license to enable 802.3af PoE Output Ports.

USB Power Input	No
Nominal Power Consumption	NA
Maximum Power Consumption	28W (w/o PoE)
Dimensions in inches	1.6 x 10.2 x 5.6 inches
Dimensions in mm	40 x 260 x 143 mm
Weight (Pound)	2.2 pounds
Weight (Gram / Kilogram)	1 kg
Operating Temperature	-40°–149°F, -40°–65°C
Humidity	15%–95% (non-condensing)
Rack-mount	No
Dual Hot Swap Power Supply	No

Warranty Info

Warranty	1-Year Limited Warranty
----------	-------------------------