



Quick Look

Number of Ethernet WAN port	2-5 (GE)	
Number of Ethernet LAN port	3-6 (GE)	
Router Throughput	1.5Gbps [2]	[2] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (No Encryption)	200Mbps [2]	[2] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (256-bit AES)	200Mbps [2]	[2] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
Number of Cellular Modem	No	

Interfaces

Maximum Ethernet WAN / LAN port configuration	5 WAN with 3 LAN, 2 WAN with 6 LAN	
SFP LAN / WAN	No	
Serial Interface	No	
Wi-Fi AP	No	
Wi-Fi WAN	No	
USB WAN	Yes (1x USB) [1]	[1] 2x USB port but only one USB WAN port can be used at a time.

Module Expansion	No
------------------	----

Performance

Maximum Number of Controlled AP / Switch	100
--	-----

Number of Recommended Users	300-1000
-----------------------------	----------

Wireless details

Cellular Modem Category options	No
---------------------------------	----

5G support	No
------------	----

SIM Slots	No
-----------	----

SIM Card Size	No
---------------	----

Wi-Fi Radio	No
-------------	----

Wi-Fi Antenna Transmit Power (2.4GHz, single chain)	No
---	----

Wi-Fi Antenna Transmit Power (5GHz, single chain)	No
---	----

Multiple SSIDs	No
----------------	----

GPS	No
-----	----

RemoteSIM (used in SIM Injector)	No
----------------------------------	----

FusionSIM	No
-----------	----

Peplink eSIM Data Plans	No
-------------------------	----

BYO eSIM	No
----------	----

Features

SpeedFusion Hot Failover	Yes
--------------------------	-----

SpeedFusion Smoothing **Yes**SpeedFusion Bandwidth Bonding **Yes**SpeedFusion Connect **Yes** ^[3]

[3] CarePlan subscription includes 500GB/year complimentary SpeedFusion Connect Usage data.

SpeedFusion Relay Mode (Server) **Yes**Drop-In Mode **Yes**High Availability **Yes**Peplink AP Series Management **Yes**Remote AP & Multiple Config Profiles Management **Yes**Switch Controller **Yes**WAN as LAN **Yes** ^[4]

[4] WAN 1 and LAN 3

LAN Bypass **Yes**InTouch **Yes**Virtual WAN **Yes**Synergy Mode (Controller) **Yes**Synergized Device **Yes**Application and Web Blocking **Yes**Web Content Filtering **Full**IP Passthrough **Yes**IPv6 **Yes**x.509 Certificate **Yes**Captive Portal **Yes**

GPIO	No
Ignition Sensing	No
Netflow Support	Yes
LACP (802.3ad) NIC Bonding	Yes
Jumbo Frame Support	Yes
Internal Storage for Edge Computing	Yes (500GB)
External Storage via USB Port	Yes ^[5]
Dead Reckoning	No

[5] Require Firmware 8.4.0 or above. Support Docker and KVM.

Core Functionality

Inter-VLAN Routing	Yes
802.1q VLANs Supported	1024
Port-Based VLAN	Yes
Load Balancing & Failover	Yes
Load Balancing Algorithms	8
Inbound Load Balancing	No
InControl 2 Cloud Management	Yes
InControl GPS Fleet Management	No

Advanced QoS Functionality

Bandwidth Usage Monitoring	Yes
QoS for VoIP and E-Commerce	Yes
User Groups Bandwidth Control	Yes

VPN Functionality

SpeedFusion VPN	Yes
Number of SpeedFusion VPN Peers	50
IPsec VPN	Yes
Number of IPsec Tunnels	100
L2TP VPN / Open VPN / PPTP VPN Server	Yes
Maximum PPTP / L2TP / OpenVPN Users	100
Remote RADIUS / LDAP authentication in Remote User Access	Yes
Number of OpenVPN Tunnel (Site to Site)	5
Number of GRE Tunnel (Site to Site)	5

Hardware

Enclosure	Indoor, Metal
4pin Molex Micro-Fit Connector	No
Terminal Block Power Connector for Mobile / Vehicular Deployment	No
AC Adapter or PSU	Power Cord (ACW-614)
Input voltage	AC 100–240V
PoE Input	No
PoE Output	No
USB Power Input	No



Nominal Power Consumption	NA
Maximum Power Consumption	50W
Dimensions in inches	16.9 x 11.9 x 1.8 inches
Dimensions in mm	431 x 305 x 44 mm
Weight (Pound)	14.6 pounds
Weight (Gram / Kilogram)	6.6 kg
Operating Temperature	32°–104°F, 0°–40°C
Humidity	NA
Rack-mount	1U
Dual Hot Swap Power Supply	No

Warranty Info

Warranty	1-Year Limited Warranty
----------	-------------------------