


SD Switch 8-Port Rugged



Specifications

RJ45 interface	8x 1GE (802.3at PoE+) [1]	[1] PoE output requires a minimum of 48V power input.
SFP / SFP+ interface	2x 1G SFP	
VLAN Groups	Yes	
Switch Capacity	20 Gbps	
Maximum Packet Forwarding Rate	14.9 Mpps	
MAC Address Table	8000	
Inter-VLAN Routing	No	
Power Supply Unit	1x PSU 120W, [2] AC Input: 100V – 240V, DC Output: 54V	[2] The bundled PSU provides 90W of PoE power budget. If you require 240W of power budget, please add 180W PSU (ACW-630) to your device.
Power Input	2x Power DIN: 54V DC, Terminal Block: 12V – 56V DC	
Power Consumption	20W (System)	
Total PoE Power Budget	90W or up to 240W [3]	[3] If you require 240W of power budget, please add 180W PSU (ACW-630) to your device
Dimensions in inches (D x W x H)	8.2 x 6.3 x 1.7 inches	
Dimensions in mm (D x W x H)	210 x 160 x 43 mm	
Weight (Pound)	2.2 pounds	



Weight (Kilogram)	1.0 kg
Operating Temperature	-40°F – 149°F, -40°C – 65°C
Humidity	15% – 95% (non-condensing)
Warranty	1-Year Limited Warranty