



## Quick Look

Number of Ethernet WAN port	<b>2-7 (GE)</b>	
Number of Ethernet LAN port	<b>3-8 (GE)</b>	
Router Throughput	<b>2.5Gbps</b> <sup>[2]</sup>	[2] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (No Encryption)	<b>400Mbps</b> <sup>[2]</sup>	[2] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (256-bit AES)	<b>400Mbps</b> <sup>[2]</sup>	[2] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
Number of Cellular Modem	<b>No</b>	

## Interfaces

Maximum Ethernet WAN / LAN port configuration	<b>7 WAN with 3 LAN, 2 WAN with 8 LAN</b>	
SFP LAN / WAN	<b>No</b>	
Serial Interface	<b>No</b>	
Wi-Fi AP	<b>No</b>	
Wi-Fi WAN	<b>No</b>	
USB WAN	<b>Yes (1x USB)</b> <sup>[1]</sup>	[1] 2x USB port but only one USB WAN port can be used at a time.

Module Expansion	<b>No</b>
------------------	-----------

## Performance

---

Maximum Number of Controlled AP / Switch	<b>250</b>
--	------------

Number of Recommended Users	<b>500-2000</b>
-----------------------------	-----------------

## Wireless details

---

Cellular Modem Category options	<b>No</b>
---------------------------------	-----------

5G support	<b>No</b>
------------	-----------

SIM Slots	<b>No</b>
-----------	-----------

SIM Card Size	<b>No</b>
---------------	-----------

Wi-Fi Radio	<b>No</b>
-------------	-----------

Wi-Fi Antenna Transmit Power (2.4GHz, single chain)	<b>No</b>
---	-----------

Wi-Fi Antenna Transmit Power (5GHz, single chain)	<b>No</b>
---	-----------

Multiple SSIDs	<b>No</b>
----------------	-----------

GPS	<b>No</b>
-----	-----------

RemoteSIM (used in SIM Injector)	<b>No</b>
----------------------------------	-----------

FusionSIM	<b>No</b>
-----------	-----------

Peplink eSIM Data Plans	<b>No</b>
-------------------------	-----------

BYO eSIM	<b>No</b>
----------	-----------

## Features

---

SpeedFusion Hot Failover	<b>Yes</b>
--------------------------	------------

SpeedFusion Smoothing	<b>Yes</b>	
SpeedFusion Bandwidth Bonding	<b>Yes</b>	
SpeedFusion Connect	<b>Yes</b> <sup>[3]</sup>	[3] CarePlan subscription includes 500GB/year complimentary SpeedFusion Connect Usage data.
SpeedFusion Relay Mode (Server)	<b>Yes</b>	
Drop-In Mode	<b>Yes</b>	
High Availability	<b>Yes</b>	
Peplink AP Series Management	<b>Yes</b>	
Remote AP & Multiple Config Profiles Management	<b>Yes</b>	
Switch Controller	<b>Yes</b>	
WAN as LAN	<b>Yes</b> <sup>[4]</sup>	[4] WAN 1 and LAN 3
LAN Bypass	<b>Yes</b>	
InTouch	<b>Yes</b>	
Virtual WAN	<b>Yes</b>	
Synergy Mode (Controller)	<b>Yes</b>	
Synergized Device	<b>Yes</b>	
Application and Web Blocking	<b>Yes</b>	
Web Content Filtering	<b>Full</b>	
IP Passthrough	<b>Yes</b>	
IPv6	<b>Yes</b>	
x.509 Certificate	<b>Yes</b>	
Captive Portal	<b>Yes</b>	

GPIO	No
Ignition Sensing	No
Netflow Support	Yes
LACP (802.3ad) NIC Bonding	Yes
Jumbo Frame Support	Yes
Internal Storage for Edge Computing	Yes (1TB)
External Storage via USB Port	Yes <sup>[5]</sup>
Dead Reckoning	No

[5] Require Firmware 8.4.0 or above. Support Docker and KVM.

## Core Functionality

---

Inter-VLAN Routing	Yes
802.1q VLANs Supported	1024
Port-Based VLAN	Yes
Load Balancing & Failover	Yes
Load Balancing Algorithms	8
Inbound Load Balancing	No
InControl 2 Cloud Management	Yes
InControl GPS Fleet Management	No

## Advanced QoS Functionality

---

Bandwidth Usage Monitoring	Yes
QoS for VoIP and E-Commerce	Yes
User Groups Bandwidth Control	Yes

## VPN Functionality

---

SpeedFusion VPN	<b>Yes</b>
Number of SpeedFusion VPN Peers	<b>300</b>
IPsec VPN	<b>Yes</b>
Number of IPsec Tunnels	<b>200</b>
L2TP VPN / Open VPN / PPTP VPN Server	<b>Yes</b>
Maximum PPTP / L2TP / OpenVPN Users	<b>200</b>
Remote RADIUS / LDAP authentication in Remote User Access	<b>Yes</b>
Number of OpenVPN Tunnel (Site to Site)	<b>5</b>
Number of GRE Tunnel (Site to Site)	<b>5</b>

## Hardware

---

Enclosure	<b>Indoor, Metal</b>
4pin Molex Micro-Fit Connector	<b>No</b>
Terminal Block Power Connector for Mobile / Vehicular Deployment	<b>No</b>
AC Adapter or PSU	<b>Power Cord (ACW-614)</b>
Input voltage	<b>AC 100–240V</b>
PoE Input	<b>No</b>
PoE Output	<b>No</b>
USB Power Input	<b>No</b>

Nominal Power Consumption	<b>NA</b>
Maximum Power Consumption	<b>70W</b>
Dimensions in inches	<b>16.9 x 11.9 x 1.8 inches</b>
Dimensions in mm	<b>431 x 305 x 44 mm</b>
Weight (Pound)	<b>12.1 pounds</b>
Weight (Gram / Kilogram)	<b>5.5kg</b>
Operating Temperature	<b>32°–104°F, 0°–40°C</b>
Humidity	<b>NA</b>
Rack-mount	<b>1U</b>
Dual Hot Swap Power Supply	<b>No</b>

## Warranty Info

---

Warranty	<b>1-Year Limited Warranty</b>
----------	--------------------------------