Tech Specs | Legacy Products

SD Switch 8-Port Rugged

Specifications

RJ45 interface	**8x 1GE (802.3at PoE+)** [1]
SFP / SFP+ interface	**2x 1G SFP**
VLAN Groups	**Yes**
Switch Capacity	**20 Gbps**
Maximum Packet Forwarding Rate	**14.9 Mpps**
MAC Address Table	**8000**
Inter-VLAN Routing	**No**
Power Supply Unit	**1x PSU 120W,** [2] **AC Input: 100V – 240V,** **DC Output: 54V**
Power Input	**2x Power DIN: 54V DC,** **Terminal Block: 12V – 56V DC**
Power Consumption	**20W (System)**
Total PoE Power Budget	**90W or up to 240W** [3]
Dimensions in inches (D x W x H)	**8.2 x 6.3 x 1.7 inches**
Dimensions in mm (D x W x H)	**210 x 160 x 43 mm**
Weight (Pound)	**2.2 pounds**

[1] PoE output requires a minimum of 48V power input.

[2] The bundled PSU provides 90W of PoE power budget. If you require 240W of power budget, please add 180W PSU (ACW-630) to your device.

[3] If you require 240W of power budget, please add 180W PSU (ACW-630) to your device

Copyright © 2026 Peplink Pte. Limited. All Rights Reserved.

Weight (Kilogram)	**1.0 kg**
Operating Temperature	**-40°F – 149°F,** **-40°C – 65°C**
Humidity	**15% – 95% (non-condensing)**
Warranty	**1-Year Limited Warranty**

Copyright © 2026 Peplink Pte. Limited. All Rights Reserved.