



Quick Look

Number of Ethernet WAN port	1 (GE)	
Number of Ethernet LAN port	4 (GE)	
Router Throughput	900Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (No Encryption)	100Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (256-bit AES)	60Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
Number of Cellular Modem	2	

Interfaces

Maximum Ethernet WAN / LAN port configuration	1 WAN with 4 LAN
SFP LAN / WAN	No
Serial Interface	No
Wi-Fi AP	Yes
Wi-Fi WAN	Yes
USB WAN	No

Module Expansion **No**

Performance

Number of Recommended Users **1-60**

Maximum Number of Controlled AP / Switch **30 / 50** ^[2]

^[2] 50 AP is available as a license add-on (AP-LC-50).

Wireless details

Cellular Modem Category options **2x CAT-6 (EU),
2x CAT-7 (US),
2x CAT-7**

5G support **No**

SIM Slots **4**

SIM Card Size **Nano-SIM (4FF)**

Wi-Fi Radio **Dual (2.4GHz + 5GHz),
2x2 Wi-Fi 5**

Wi-Fi Antenna Transmit Power (2.4GHz, single chain) **25dBm**

Wi-Fi Antenna Transmit Power (5GHz, single chain) **25dBm**

Multiple SSIDs **16**

GPS **Yes**

RemoteSIM (used in SIM Injector) **Yes**

FusionSIM **Yes**

Peplink eSIM Data Plans **Yes** ^[3]

^[3] Require Firmware 8.3.0 or above and supported for selected SKU.

BYO eSIM **Yes** ^[4]

^[4] Require Firmware 8.4.0 or above and supported for selected SKU.

Features

SpeedFusion Hot Failover	Yes ^[5]	[5] Require PrimeCare Subscription, complimentary for the first year.
SpeedFusion Smoothing	Yes ^[5]	[5] Require PrimeCare Subscription, complimentary for the first year.
SpeedFusion Bandwidth Bonding	Yes ^[5]	[5] Require PrimeCare Subscription, complimentary for the first year.
SpeedFusion Connect	Yes ^[6]	[6] PrimeCare subscription includes 500GB/year complimentary SpeedFusion Connect Usage data.
SpeedFusion Relay Mode (Server)	Yes	
Drop-In Mode	Yes	
High Availability	Yes	
Peplink AP Series Management	Yes	
Remote AP & Multiple Config Profiles Management	No	
Switch Controller	Yes	
WAN as LAN	No	
LAN Bypass	No	
InTouch	Yes	
Virtual WAN	Yes ^[7]	[7] 1 Virtual WAN complimentary with active PrimeCare. Up to 3 Virtual WAN upon purchasing Virtual WAN Activation Licence.
Synergy Mode (Controller)	Yes	
Synergized Device	Yes	
Application and Web Blocking	Yes	
Web Content Filtering	Lite	
IP Passthrough	Yes ^[8]	[8] Available for Firmware 8.5.0 or above.
IPv6	No	
x.509 Certificate	Yes	

Captive Portal	Yes
GPIO	Yes
Ignition Sensing	Yes
Netflow Support	Yes
LACP (802.3ad) NIC Bonding	No
Jumbo Frame Support	No
Internal Storage for Edge Computing	No
External Storage via USB Port	No
Dead Reckoning	No

Core Functionality

Inter-VLAN Routing	Yes
802.1q VLANs Supported	16
Port-Based VLAN	Yes
Load Balancing Algorithms	8
Load Balancing & Failover	Yes
Inbound Load Balancing	No
InControl 2 Cloud Management	Yes
InControl GPS Fleet Management	Yes

Advanced QoS Functionality

Bandwidth Usage Monitoring	Yes
QoS for VoIP and E-Commerce	Yes

User Groups Bandwidth Control **Yes**

VPN Functionality

SpeedFusion VPN **Yes**

Number of SpeedFusion VPN Peers **2 or 5** ^[9]

[9] 2 SpeedFusion VPN Peers are enabled by default. 5 SpeedFusion VPN Peers are enabled with PrimeCare Subscription, complimentary for the first year.

IPsec VPN **Yes**

Number of IPsec Tunnels **5**

L2TP VPN / Open VPN / PPTP VPN Server **Yes**

Maximum PPTP / L2TP / OpenVPN Users **3**

Remote RADIUS / LDAP authentication in Remote User Access **No**

Number of OpenVPN Tunnel (Site to Site) **5**

Number of GRE Tunnel (Site to Site) **5**

Hardware

Enclosure **Indoor, Metal**

4pin Molex Micro-Fit Connector **Yes**

Terminal Block Power Connector for Mobile / Vehicular Deployment **No**

AC Adapter or PSU **AC Input 100V–240V, DC Output 12V 2A**

Input voltage **DC 10–30V**

PoE Input **No**

PoE Output	No
USB Power Input	No
Nominal Power Consumption	NA
Maximum Power Consumption	24W
Dimensions in inches	6.8 x 6.3 x 1.2 inches
Dimensions in mm	171.8 x 166.2 x 29.3 mm
Weight (Pound)	1.59 pounds
Weight (Gram / Kilogram)	720 grams
Operating Temperature	-40°–149°F, -40°–65°C
Humidity	15%–95% (non-condensing)
Rack-mount	No
Dual Hot Swap Power Supply	No

Warranty Info

Warranty	1-Year Limited Warranty
----------	-------------------------