

SD Switch 16-Port Rugged



Specifications

RJ45 interface	8x 1GE (802.3at PoE+), [1] 8x 1GE Ports	[1] PoE output requires a minimum of 48V power input.
SFP / SFP+ interface	2x 1G SFP	
VLAN Groups	Yes	
Switch Capacity	36 Gbps	
Maximum Packet Forwarding Rate	26.8 Mpps	
MAC Address Table	8000	
Inter-VLAN Routing	No	
Power Supply Unit	1x PSU 120W, [2] AC Input: 100V – 240V, DC Output: 54V	[2] The bundled PSU provides 90W of PoE power budget. If you require 240W of power budget, please add 180W PSU (ACW-630) to your device.
Power Input	2x Power DIN: 54V DC, Terminal Block: 12V – 56V DC	
Power Consumption	20W (System)	
Total PoE Power Budget	70W or up to 240W [3]	[3] If you require 240W of power budget, please add 180W PSU (ACW-630) to your device.
Dimensions in inches (D x W x H)	7.5 x 9.0 x 1.5 inches	
Dimensions in mm (D x W x H)	190 x 226 x 35 mm	
Weight (Pound)	4.4 pounds	



Weight (Kilogram)	2.0 kg
Operating Temperature	-40°F – 149°F, -40°C – 65°C
Humidity	15% – 95% (non-condensing)
Warranty	1-Year Limited Warranty