



## Quick Look

Number of Ethernet WAN port	<b>1 / 0 (GE)</b> <sup>[1]</sup>	[1] WAN port(s) can be configured as LAN port(s) via the Web Admin.
Number of Ethernet LAN port	<b>3 / 4 (GE)</b> <sup>[1]</sup>	[1] WAN port(s) can be configured as LAN port(s) via the Web Admin.
Router Throughput	<b>400Mbps</b> <sup>[2]</sup>	[2] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (No Encryption)	<b>100Mbps</b> <sup>[2]</sup>	[2] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (256-bit AES)	<b>60Mbps</b> <sup>[2]</sup>	[2] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
Number of Cellular Modem	<b>1 or 2</b>	

## Interfaces

Maximum Ethernet WAN / LAN port configuration	<b>1 WAN with 3 LAN, 0 WAN with 4 LAN</b>
SFP LAN / WAN	<b>No</b>
Serial Interface	<b>Yes</b>
Wi-Fi AP	<b>No</b>
Wi-Fi WAN	<b>No</b>
USB WAN	<b>No</b>

Module Expansion **No**

## Performance

---

Number of Recommended Users **25-150**

Maximum Number of Controlled AP / Switch **30 / 50** <sup>[3]</sup>

[3] 50 AP is available as a license add-on (AP-LC-50).

## Wireless details

---

Cellular Modem Category options **2x CAT-7,  
2x CAT-12,  
1x 5G (US)**

5G support **Yes**

SIM Slots **4**

SIM Card Size **Mini-SIM (2FF)**

Wi-Fi Radio **No**

Wi-Fi Antenna Transmit Power (2.4GHz, single chain) **No**

Wi-Fi Antenna Transmit Power (5GHz, single chain) **No**

Multiple SSIDs **No**

GPS **Yes**

RemoteSIM (used in SIM Injector) **Yes**

FusionSIM **Yes**

Peplink eSIM Data Plans **No**

BYO eSIM **No**

## Features

---

SpeedFusion Hot Failover	<b>Yes</b> <sup>[4]</sup>	[4] Require PrimeCare Subscription, complimentary for the first year.
SpeedFusion Smoothing	<b>Yes</b> <sup>[4]</sup>	[4] Require PrimeCare Subscription, complimentary for the first year.
SpeedFusion Bandwidth Bonding	<b>Yes</b> <sup>[4]</sup>	[4] Require PrimeCare Subscription, complimentary for the first year.
SpeedFusion Connect	<b>Yes</b> <sup>[5]</sup>	[5] CarePlan subscription includes 1TB/year complimentary SpeedFusion Connect Usage data.
SpeedFusion Relay Mode (Server)	<b>Yes</b>	
Drop-In Mode	<b>Yes</b>	
High Availability	<b>Yes</b>	
Peplink AP Series Management	<b>Yes</b>	
Remote AP & Multiple Config Profiles Management	<b>No</b>	
Switch Controller	<b>Yes</b>	
WAN as LAN	<b>Yes</b>	
LAN Bypass	<b>No</b>	
InTouch	<b>Yes</b>	
Virtual WAN	<b>Yes</b> <sup>[6]</sup>	[6] Up to 3 Virtual WAN if purchasing Virtual WAN Activation Licence.
Synergy Mode (Controller)	<b>Yes</b>	
Synergized Device	<b>Yes</b>	
Application and Web Blocking	<b>Yes</b>	
Web Content Filtering	<b>Lite</b>	
IP Passthrough	<b>Yes</b> <sup>[7]</sup>	[7] Available for Firmware 8.5.0 or above.
IPv6	<b>Yes</b>	
x.509 Certificate	<b>No</b>	

Captive Portal	<b>Yes</b>
GPIO	<b>Yes</b>
Ignition Sensing	<b>Yes</b>
Netflow Support	<b>Yes</b>
LACP (802.3ad) NIC Bonding	<b>No</b>
Jumbo Frame Support	<b>No</b>
Internal Storage for Edge Computing	<b>No</b>
External Storage via USB Port	<b>No</b>
Dead Reckoning	<b>No</b>

## Core Functionality

---

Inter-VLAN Routing	<b>Yes</b>
802.1q VLANs Supported	<b>128</b>
Port-Based VLAN	<b>Yes</b>
Load Balancing Algorithms	<b>8</b>
Load Balancing & Failover	<b>Yes</b>
Inbound Load Balancing	<b>No</b>
InControl 2 Cloud Management	<b>Yes</b>
InControl GPS Fleet Management	<b>Yes</b>

## Advanced QoS Functionality

---

Bandwidth Usage Monitoring	<b>Yes</b>
QoS for VoIP and E-Commerce	<b>Yes</b>

User Groups Bandwidth Control **Yes**

## VPN Functionality

---

SpeedFusion VPN **Yes**

Number of SpeedFusion VPN Peers **2 or 5** <sup>[8]</sup>

[8] 2 SpeedFusion VPN Peers are enabled by default. 5 SpeedFusion VPN Peers are enabled with PrimeCare Subscription, complimentary for the first year.

IPsec VPN **Yes**

Number of IPsec Tunnels **5**

L2TP VPN / Open VPN / PPTP VPN Server **Yes**

Maximum PPTP / L2TP / OpenVPN Users **3**

Remote RADIUS / LDAP authentication in Remote User Access **No**

Number of OpenVPN Tunnel (Site to Site) **5**

Number of GRE Tunnel (Site to Site) **5**

## Hardware

---

Enclosure **Indoor, Metal**

4pin Molex Micro-Fit Connector **Yes**

Terminal Block Power Connector for Mobile / Vehicular Deployment **Yes**

AC Adapter or PSU **AC Input 100V-240V, DC Output 12V 2A**

Input voltage **DC 12-56V**

PoE Input **No**

PoE Output	<b>1x 802.3at PoE+ (up to 25.5W)</b>
USB Power Input	<b>No</b>
Nominal Power Consumption	<b>8W</b>
Maximum Power Consumption	<b>18W</b>
Dimensions in inches	<b>6.3 x 3.8 x 1.3 inches</b>
Dimensions in mm	<b>160 x 97 x 33.5 mm</b>
Weight (Pound)	<b>1.3 pounds</b>
Weight (Gram / Kilogram)	<b>590 grams</b>
Operating Temperature	<b>-40°–149°F, -40°–65°C</b>
Humidity	<b>15%–95% (non-condensing)</b>
Rack-mount	<b>No</b>
Dual Hot Swap Power Supply	<b>No</b>

## Warranty Info

---

Warranty	<b>1-Year Limited Warranty</b>
----------	--------------------------------