

SD Switch 24-Port Rugged



Specifications

RJ45 interface	24x 1GE (802.3at PoE+)	
SFP / SFP+ interface	2x 10G SFP+	
VLAN Groups	Yes	
Switch Capacity	88 Gbps	
Maximum Packet Forwarding Rate	66 Mpps	
MAC Address Table	32000	
Inter-VLAN Routing	Yes	
Power Supply Unit	1x PSU 180W, ^[1] AC Input: 100V – 240V, DC Output: 54V	[1] The bundled PSU provides 120W of PoE power budget. If you require 250W of power budget, please add 180W PSU (ACW-630) to your device.
Power Input	2x Power DIN: 54V DC, Terminal Block: 12V – 54V DC	
Power Consumption	50W (System)	
Total PoE Power Budget	70W or up to 250W ^[2]	[2] If you require 250W of power budget, please add 180W PSU (ACW-630) to your device
Dimensions in inches (D x W x H)	10.5 x 19.1 x 1.7 inches	
Dimensions in mm (D x W x H)	265 x 485 x 45mm	
Weight (Pound)	11.3 pounds	

Weight (Kilogram)	5.14 kg
Operating Temperature	-40°F – 149°F, -40°C – 65°C
Humidity	15% – 95% (non-condensing)
Warranty	1-Year Limited Warranty